



- NOTES:
- THIS DRAWING FILED IN CCD.
  - SINGLE CONDUCTOR WIRE PER MIL-W-81044/12-XX-9 SHIELDED PAIR PER M27500--ML2108 TWISTED PAIR PER M27500--ML2100 (\*=22 AWG, EXCEPT AS NOTED.)
  - FOR GND/BLOCK STUD LOCATIONS, REFER TO GND/BLOCK STUD INSTL DWG CALLED OUT ON AVIONICS INSTL KIT.
  - GROUND MUST BE WITHIN 12" OF PIN 17.
  - AN ASTERISK INDICATES LOWER CASE.
  - LENGTH OF WIRE SUPPLIED WITH REMOTE AREA MICROPHONE (HARD WIRED TO MIC).
  - REFER TO P/L NOTE 2.
  - REFER TO P/L NOTE 1 FOR CABLE PART NUMBER.
  - PERMISSIBLE FOR WIRE(S) TO DEVIATE FROM HIRF REQUIREMENTS DEFINED BY CSAM012.
  - PERMISSIBLE FOR BRAIDED SHIELD CONNECTIONS TO BE SUBSTITUTED BY 22AWG WIRE FROM THE SOLDER SLEEVE.

DATE	05/30/03	CESSNA AIRCRAFT COMPANY
DRAWN	K. BURTON	AIRCRAFT DIVISION
CHECK		P. O. BOX 7704
GROUP		WICHITA, KANSAS 67277
SECT		
PROJ		
M.E.		
OTHER		
FABRICATE PER CSAM012	SIZE FSCM NO.	8622113
PROCESS PER 33XXXXXXX	SCALE:	PARENT 8622112 SHEET 1 OF 1
WIRE TERMINATION PER 352216		

8622113  
EC 52743